

Hill-Rom.

Liko™ Likorall™ 242 ES/S | 243 ES | 250 ES/S IRC Overhead lift motor



Safe and flexible overhead lift motor.

Thanks to user-friendliness, a genuine regard for safety and clever design, the Likorall™ overhead lift motor is highly regarded among both care staff and patients.

Likorall's combination of unique technology, operational reliability and ease of maintenance, together with Liko's wide range of accessories, make it possible for Likorall™ to accommodate almost any lifting situation imaginable.

Let your needs decide!

Likorall™ is not simply an overhead lift motor; it is a part of family of lift units with many helpful features. The lifting capacity ranges from 200 to 500 kg. The flexibility with which Liko's rail systems can be installed and the possibility of choosing a freestanding system mean that Likorall™ can be used in any care setting.

With Likorall™, charging is possible along the rail, and the system can be equipped with wireless IR control, a transfer motor and electrical track switches.

Important features

- Patented safety drum SFS
- Lift strap with ten-fold safety margin and fitted with the SSP limit switch for squeeze protection
- Electrical emergency lowering and raising
- Three different ways of charging:
 - handcontrol
 - continual rail charging
 - multiStation
- Fixtures with four-fold safety factor



A carriage adapter makes it possible to move the lift motor simply and easily between different rail systems, without the use of tools.



Slings adapted to all possible lifting situations; Liko™ has one of the world's largest assortments.



With LikoScale, weighing patients in the lift is easy and convenient. With the scale in a quick-release hook, it can be easily moved when necessary.



Slingbars adapted to different lifting situations, easily exchangeable, thanks to Liko's quick-release hook system.

...for more accessories, please visit www.liko.com

Maximum load:

Likorall™ 242 ES/S	200 kg
Likorall™ 243 ES	230 kg
Likorall™ 250 ES/ S IRC	250 kg

Lift interval: 200 cm

Motor: 24 V, 12 A

Batteries: 2 x 12 V 2.6 Ah
valve-regulated lead-acid gel-type batteries

Battery charger: 100-240 VAC 40-60 Hz, max 600 mA

Product number:

3122005	Likorall™ 242 ES	natural	3123001	Likorall™ 243 ES	natural
3122006	Likorall™ 242 ES	white	3123002	Likorall™ 243 ES	white
3122009	Likorall™ 242 S	natural	3122501	Likorall™ 250 ES	natural
3122010	Likorall™ 242 S	white	3122502	Likorall™ 250 ES	white
3122007	Likorall™ 242 ES R2R	natural	3124050	Likorall™ 250 S IRC	natural
3122008	Likorall™ 242 ES R2R	white			
3122011	Likorall™ 242 S R2R	natural			
3122012	Likorall™ 242 S R2R	white			



Likorall™ has been tested by an accredited testing institute and complies with the requirements of the Medical Device Directive for Class I products (MDD 93/42/EEC) Likorall™ complies with the requirements of IEC 60601-1, IEC 60601-1-2, EN ISO 10535, UL-60601-1 and CAN/CSA C22.2 No.601.1.

Design and Quality by Liko in Sweden.

Liko is quality certified in accordance with ISO 9001 and its equivalent for the medical device industry, ISO 13485. Liko is also certified in accordance with environmental standard ISO 14001.

Hill-Rom is a trademark or registered trademark of Hill-Rom Services Inc. Liko is a trademark or registered trademarks of Liko R&D AB. Likorall is a trademark or registered trademark of Liko R&D AB.



Enhancing Outcomes for Patients and Their Caregivers.™

France _____ +33 (0)2 97 50 92 12
 United Kingdom _____ +44 (0)1530 411000
 Deutschland _____ +49 (0)211 16450-0
 Nederland _____ +31 (0)347 32 35 32
 Italia _____ + 39 (0)2 950541
 Suisse/Schweiz _____ +41 (0)21 706 21 30
 (deutschsprachig) _____ +41 (0)21 706 21 38

Österreich _____ +43 (0)2243 28550
 Ireland _____ +353 (0)1 413 6005
 Iberia _____ +34 (0)93 6856000
 Nordic Countries _____ +46 (0)20 78 10 30
 Export _____ Contact your local Hill-Rom distributor or contact your Area Manager via website or call _____ +1 812 934 8173

www.hill-rom.com
www.liko.com

Hill-Rom® reserves the right to make changes without notice in design, specifications and models. The only warranty Hill-Rom® makes is the express written warranty extended on the sale or rental of its products.
 © 2012 Hill-Rom® SARL, ALL RIGHTS RESERVED.